

KEEP YOUR DEPOSITS
SAFE RETAIL AND
COMMERCIAL PREMISES





RHINO MK II DT





KEY FEATURES

- Designed for retail and commercial use.
- 65mm barrier thickness made of a highdensity monolithic casting contained within inner and outer steel casings.
- Solid composite 35mm thick main door is combined with additional protection plates to protect crucial locking areas. Solid steel 28.5 mm diameter moving bolts attach the door to the body, while fixed "anti-heeling" bolts on the door's rear edge protect the hinge side.
- Deposit drawer with solid 10mm steel plate front combined with an internal anti-fishing mechanism to secure all items deposited.
- Main door secured by EN 1300 Class A
 primary locks which can be single lock, be it a
 key lock, manual combination or electronic
 lock depending upon individual
 requirements. For additional security, a
 second lock is possible.
- Drawer deposit unit secured by a single EN

 1200 costified Class A lock
- Two security fixing bolts to ensure it can be firmly fixed to the floor when installed.
- Deposit drawer capable of accepting items measuring up to 40mm high x 100mm wide x 240mm deep. Small envelopes, cassettes and bags can all be accommodated, but to avoid entanglement with the anti-fishing device, bags should be clean and in good condition and should not have any tears, rips or security seals.



RHINO MK II DT

PRODUCT SPECIFICATIONS

Model	External height(mm)	External width(mm)	External depth(mm)	Internal height(mm)	Internal width(mm)	Internal depth(mm)	Volume (litres)	Weight (kg)	Moving Front Bolts	Fixed Back Bolts
Size 1	654	500	502	270	370	320	40		2	2
Size 2	854	500	502	470	370	320	56		3	3
Size 3	1004	500	502	620	370	320	73		3	3
Size 4	1004	630	602	620	500	420	130		3	3
Size 5	1234	630	602	850	500	420	179		4	4

MAXIMUM SIZE OF DEPOSIT PACKAGE

Height: 40mm Width: 500mm Depth: 502mm

www.chubbsafes.com

MARKETED BY **GUNNEBO**°





