

INNOVATIVE SAFE FOR COMBINED BURGLARY AND FIRE PROTECTION



DUOGUARD

BURGLARY- & FIRE-RESISTANT PROTECTION





- Burglary protection in accordance with the European standard, EN 1143-1, as certified by ECB•S for Grades 0 and I.
- Approved by ECB•S in accordance with EN 1047-1 in class S 60 P for one hour's fire protection of paper documents.
- Torch-resistant barrier material Dualite

 ensures burglary and fire protection
 whilst also reducing its total weight and
 minimising transportation and installation costs.
- The three-way boltwork is constructed with solid steel bolts.
- Fitted with an active relocker and antidrilling plates incorporated into the boltwork to withstand burglary attempts. (manganese-coated steel plates for Grade 0 and T200X carbide-clad steel plates for Grade I).
- A Class A mechanical key lock or a Class B high-security electronic lock, approved in accordance with EN 1300, are both
- available as primary lock options. Electronic locks increase the level of security and prevent unauthorised access to the safe.
- Ergonomic soft-touch handle and a wide range of internal fittings to maximise storage capacity.
- A data media insert is available, certified 60 Diskette by NT Fire 017, for one hour's fire protection of heat-sensitive data media.



DUOGUARD

PRODUCT SPECIFICATIONS

INTERNAL FITTINGS

	EXTERNAL (mm)			INTERNAL (mm)				
Model			Depth			Depth		
40	435	500	456	335	400	295	40	90
60	530	500	521	430	400	360	62	115
110	690	600	561	590	500	386	114	161
150	875	600	561	775	500	386	150	196
200	1150	600	561	1050	500	386	203	243
300	1600	600	561	1500	500	386	290	322
350	1600	675	585	1500	575	410	354	352
450	1850	675	615	1750	575	440	443	415



Suspension file frame



Extendable tray



Shelf




Extendable shelf



Extendable drawer



Lockable compartment





Data media insert

Shelf for hanging files (available for size 110 and above)

LOCK OPTIONS



safes can be fitted with either a high-security electronic lock (Class B) or a key lock (Class A).

up. The primary lock can be complemented by a combination lock or both a key lock and electronic lock can be fitted.

- 1 master code, 1 supervisor code and 7 user codes.
- Time delay of up to 99 minutes between lock being operated and
- Protective function to raise silent alarm if lock is being opened under duress.

TESTING

FIRE TESTING

DuoGuard has been approved in accordance with the European protect paper documents for one hour. This certification was awarded by ECB•S (European Certification Board•Security Systems).

TEST PROCEDURE

Stage 1

The cabinet is placed in a furnace and heated to a temperature of almost 1000°C for 60 minutes to simulate the effects of a severe fire.

Stage 2

BURGLARY TESTING

A range of attack tools were used to test DuoGuard's level of resistance, from basic tools to sophisticated thermal and electrical

www.chubbsafes.com

MARKETED BY **GUNNEBO**°

Chubbsafes

Trusted the world over.



Showroom: Near to Avenues

Al Rai, Hamad Rashed Al Alban Street Opp. to Party Land. Fax: +965 24773210. Mob: +965 66955617 / 65700890



المعرض : قريب من الافنيوز الري، شارع حمد راشد العلبان، مقابل بارتی لاند. هاکس: ۲٤٧٧٣٢١٠ ٩٦٥ ت: ۱۱۲۰۰۹۲ / ۹۱۸۰۰۷۰۲ + ۱۹۲۰

Email: info@kaavalkuwait.com, www.kaavalkuwait.com

Office: Farwaniya

Megateer Complex, 2nd Floor, Office # 15 Habeeb Munawer Street, Kuwait. Tel / Fax: +965 24773210 / 66955617



المكتب : الفروانيه مكتب رقم ١٥، مجمّع مغاتير، الدور ٢، ش حبيب المناور ، الكويت ت / فاکس: ۱۲۲۰۰۱۲ / ۲۲۲۷۳۲۱۰ + ۹۹۵

